



IMPREGNATING SEALER IDEAL FOR WORK TOPS

Solvent-based stain protection, superb on glossy and polished surfaces, performing on high absorption surfaces too. Superb for work tops whose maintenance and restoration it makes easier.


SOLVENT BASE

NATURAL EFFECT

APPROVED FOR FOOD CONTACT

TECHNICAL CHARACTERISTICS

Water-oil repellent, water-based stain protection. Penetrates and settles in the microporosities of the material protecting it from any kind of dirt, without altering the natural breathability of the material. Superb protection also on high porosity materials that are protected completely and homogeneously. Designed to offer great protection to quartzite work tops whose maintenance and restoration it makes easier.

HOW TO APPLY IT

Tools



By paintbrush, spraying, with a cloth or sponge.

Mode

The product must be applied on perfectly dry and clean surfaces, by paintbrush, spraying, with a cloth or sponge. Non-absorbent surfaces: Remove from the surface any product excess with a clean cloth one minute after applying it. For best results, repeat the treatment after about 10-15 minutes from the first application. In rare cases, it can enhance the colour of the material.

High absorption materials

(i.e. Quartzite): two hours after applying it, remove any product excess from the surface with a cloth soaked with a little product. Then, standardise the surface to prevent the formation of any residue. The desired stain-resistant effect is reached 24 hours after the treatment. In case of floors, wait at least 24 hours before walking on the floor.

WHERE TO APPLY IT

- GRANITE**
- MARBLE**
- NATURAL STONES**
quartzite, limestone, sandstone
- COTTO**



PLUS/ADVANTAGES

- APPROVED FOR FOOD CONTACT**
- IDEAL FOR WORK TOPS**
- HIGH STAIN-PROTECTION EFFECT ALSO ON POROUS SUPPORTS**
- MAKES THE MAINTENANCE AND RESTORATION OF WORK TOPS EASIER**

TECHNICAL DATA

Density at 25°C gr/cm ³	0,805
Appearance	opalescent liquid
Standard colour	colourless

COVERAGE/DILUTION

The consumption depends greatly on the porosity of the material.

1L of product	
GRANITE AND MARBLE	30 m ² 323 sq.ft.
LIMESTONE AND SANDSTONE	20 m ² 215 sq.ft.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



Scans to access multimedia contributions

PACKAGING

0,25-1 litre

HOW TO STORE IT

Under normal conditions of use and work, the product stored properly away from heat, moisture and direct sunlight is guaranteed 24 months. Close carefully the packaging after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. If the surface is treated for the first time we recommended the effect and the adherence of the material on a sample or a hidden corner are assessed.

LEGISLATION

Before use please read the instructions on the safety data sheet and the following notes on the cans.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.